



## THANK YOU FOR PURCHASING

## THE SAWBONES ARTHROSCOPY ANKLE MODEL

This arthroscopy model may be used for diagnostic and visualization skills including triangulation and pathology identification. Loose body retrieval and pathology resection may also be performed. With a little care and maintenance your new model should provide you with many years of service.

## COMPONENTS & ANATOMY

### MODELS INCLUDE:

- Soft tissue foot
- Standard tibia/fibula/talus insert
- Tibia/fibula vice block
- Bone clamp
- C-clamp

**NOTE:** There are two additional replacement inserts available. See replacement parts list. All replacement parts available at [www.sawbones.com](http://www.sawbones.com)

### ANATOMICAL STRUCTURE:

- Talus, tibia, fibula basic bone anatomy.
- Transchondral fracture of dorsal medial aspect of talus.
- Transchondral fracture of dorsal posterior lateral aspect of talus.
- Chondromalacic area at the anterior aspect of tibiotalar joint.
- Transchondral fracture of distal medial anterior portion of lateral malleolar.
- Osteochondral loose bodies.



## SET-UP INSTRUCTIONS

1. Attach the bone and C-clamp combination to the table as shown.
2. Securely fasten the vice block to the bone clamp.
3. Secure the model at a 45° angle from the edge of the table.

## INSERT REMOVAL & REPLACEMENT



### BONE INSERT REMOVAL:

1. Remove the model from the bone clamp.
2. Remove the 1" Velcro strip from the soft tissue ankle.
3. Retract the Velcro strips from the vice block.
4. Remove the vice block and bone insert from the foot.



### TALUS INSERT REMOVAL/REPLACEMENT:

1. After the tibia/fibula insert has been removed, the talus may be grasped with fingers and extracted from the model.
2. To replace, reverse the procedure making sure the talus is fully seated within the model.



### FINAL ASSEMBLY:

1. Replace 1" Velcro tabs to vice block.
2. Rewrap Velcro around soft tissue ankle.

## CARE & MAINTENANCE

Your model can be wiped down with any mild cleaner. Use only the dry erase marker on the model. Standard ink can not be removed. Store in a dry, dark place out of direct contact with sunlight.

## REPLACEMENT PARTS ([WWW.SAWBONES.COM](http://WWW.SAWBONES.COM))



**1412-1**  
Talus/fibula/tibia,  
standard




**1412-2**  
Talus/fibula/tibia,  
advanced



**1412-3**  
Talus/fibula/tibia,  
advanced



**1116-23**  
Tibia/fibula vice block



**1600**  
Bone clamp



**1601**  
C-clamp